



CONTENTS

SITE LIGHTS

| MTB-5000 | Multi Battery Site Light | ŗ |
|-----------|-----------------------------------|---|
| MTB-5300 | Multi Battery 'Hybrid' Site Light | ţ |
| MTB-10000 | Multi Battery 360° Site Light | ţ |
| TL-6000 | Rechargeable Tripod Site Light | |
| SLR-5500 | 360° Site Light | |
| RL-5250 | Rechargeable Site Light | |
| SLR-4400 | Dual Power Site Light | |
| RF-5400 | Super Tough Floodlight | 9 |
| RF-3300 | Heavy Duty Floodlight | Ś |
| RF-2000 | Heavy Duty Floodlight | ç |

WORK LIGHTS

| K-550 | Compact Mini Work Light |
|----------|------------------------------|
| WL-450R | Dual Beam Compact Work Light |
| SLR-1450 | Compact Rotating Work Light |
| SLR-1750 | Work Light with Powerbank |

MISC. LIGHTS

| NL-350R | Rechargeable Neck Light | |
|---------|----------------------------|--|
| PB-7800 | Powerbank with Flashlight | |
| L-1800 | Dual LED Spotlight Lantern | |

NSPECTION LIGHTS

| IL-175R | Folding Inspection Light | 1 |
|---------|-----------------------------|---|
| IL-375R | Folding Inspection Light | 1 |
| IL-425R | Folding Inspection Light | 1 |
| IL-925R | Folding Inspection Light | 1 |
| PL-3 | Inspection Penlight | 1 |
| IL-625R | Inspection Light | 1 |
| IL-SIG1 | Signalling Inspection Light | 1 |

июи сонненте

| CRI-1250R | High CRI Inspection Light | 17 |
|-----------|-----------------------------|----|
| CRI-3350 | High CRI Site Light | 19 |
| CRI-H200R | High CRI Sensor Headtorch | 19 |
| HT-680R | Dual LED High CRI Headtorch | 1 |

| EADIONCHES | |
|------------|--------|
| T-900R | High I |
| | |

| HT-900R | High Power Industrial Headtorch | 19 |
|----------|-----------------------------------|----|
| HL-11R | Industrial Super Bright Headtorch | 21 |
| PS-HDL9R | High Power Industrial Headtorch | 21 |
| HT-650R | Dual Power Dual LED Headtorch | 21 |
| HL-8R | Dual Beam Sensor Headtorch | 21 |
| PS-HDL6R | Dual Power Helmet Headtorch | 23 |
| HL-4R | USB Helmet Headtorch | 23 |
| PS-HDL2 | Helmet Headtorch | 23 |
| BLT-1 | USB Beanie Light | 23 |
| | | |

| FLASHLIGHTS | | |
|-------------|-----------------------------------|----|
| FR-400 | Right Angle Flashlight | 25 |
| FR-1200 | Right Angle Dual Power Flashlight | 25 |
| F-1400 | Dual Power Aluminium Flashlight | 25 |
| F-2700 | USB Aluminium Flashlight | 25 |

| INTRINSICALLY SAFE TORCHES | | |
|----------------------------|--------------------------|----|
| ATEX-FL4 | Zone 0 Flashlight | 27 |
| ATEX-RA2 | Zone 0 Right Angle Torch | 27 |
| ATEX-H2 | Zone 0 Headtorch | 27 |
| | | |

| WORK WEAR | | |
|-----------|---------------------------|----|
| ZFJ | Zipped Fleece Jumper | 29 |
| LWJ | Lightweight Padded Jacket | 29 |
| WPC | Waterproof Coat | 29 |

| TOOL POUCHES | | |
|--------------|--------------------------------|----|
| OP-1B | Heavy Duty Storage Pouches | 31 |
| OP-2B | Heavy Duty Storage Pouches | 31 |
| OP-3B | Super Heavy Duty Storage Pouch | 31 |

| KNIVES & SCISSORS | | |
|-------------------|---------------------------------------|----|
| KC1 | Heavy Duty Snap-off Cutter | 33 |
| KC2 | Heavy Duty Cutter | 33 |
| UK1 | Folding Utility Knife | 33 |
| FK3 | Heavy Duty Folding Utility Knife | 35 |
| EK4 | Heavy Duty Folding Utility Knife | 35 |
| EK5 | Heavy Duty Folding Utility Knife | 35 |
| ES-6 | Heavy Duty 6" Electricians Scissors | 37 |
| MFS-8 | Heavy Duty 8" Multi-Function Scissors | 37 |

| TAPE MEASURES | | |
|---------------|----------------------------|----|
| MT5M1 | Heavy Duty 5m Tape Measure | 39 |
| MT5M4SL | Heavy Duty 5m Tape Measure | 39 |
| MT5M2 | Heavy Duty 5m Tape Measure | 39 |
| MT8M3 | Heavy Duty 8m Tape Measure | 39 |

| SAFETY GLASSES | | |
|----------------|---------------------------------|----|
| SG-YIO | Safety Glasses - Indoor/Outdoor | 41 |
| SG-YCB | Safety Glasses - Blue Light | 41 |
| SG-YDS | Safety Glasses - Dark Smoke | 41 |
| SG-YFG | Safety Glasses - Foam Gasket | 41 |

| SAFETY GLOVES | | |
|---------------|---------------------------|----|
| UG-12C4 | Impact & Cut-D Gloves | 43 |
| UG-TW1 | Thermal Waterproof Gloves | 43 |

| MAGNET & TRIPODS | | |
|------------------|--------------------------------|----|
| LARGE-MAGNET | Super Strong Magnet | 45 |
| TRIPOD-360 | Tripod with Magnetic Plate | 45 |
| TRIPOD-SW | Single Head Tripod with Wheels | 45 |
| TRIPOD-SGL | Single Head Tripod | 45 |



Unilite leads the charge in providing advanced lighting solutions tailored for trade professionals across various industries. Established in 1981 in the UK, we've evolved into a global leader by prioritising innovation, durability, and customer satisfaction.

Our commitment to innovation drives us to continuously refine our products using the latest LED technology and ultra tough materials. From rugged headtorches for outdoor work to powerful work lights for industrial settings, our comprehensive range meets the demands of the toughest job sites. Each product undergoes rigorous testing to ensure reliability and performance in challenging conditions.

At Unilite, we understand the needs of trade professionals. Our customer-centric approach means we offer more than just superior products – we're dedicated partners, providing tailored solutions with integrity and professionalism. Whether you're a construction worker, electrician, plumber, or emergency responder, we have the lighting solutions and a range of other tools and workwear to enhance safety, productivity, and efficiency in your work.

Looking ahead, Unilite Limited remains committed to innovation and sustainability, ensuring we continue to meet the evolving needs of trade professionals worldwide. Join us as we light the way to a brighter future for industrial tradespeople everywhere.

-



MTB-5000 MULTI BATTERY SITE LIGHT

5000 lumen 6500K SMD LEDs

BATTE

WEIGH

DIMEN

- 4500k / 5500k / 6500k
- Takes up to 20V 6.0Ah batteries from Milwaukee, De Walt, Makita & Metabo - 4 adapters included
- Secure battery compartment cover (note: larger cover)
- Super tough heavy duty nylon & TPR construction
- Milky diffuser lens for even light dispersion

| RY | Not included, bare tool |
|-------|-------------------------|
| Т | 1980g |
| SIONS | W 280 x H 280 x D 148r |

Easy carry rubber grip handle

 Multiple colour temperatures - CCT: 2700k / 3500k /
 150-degree rotating stand with hole for attaching tripod/magnet and feet that act as a hanging bracket

D<u>I</u>UNILITE

- IP65 Dust & water resistant
- Super heavy duty IK10 Shock proof
- 5.5Ah-6.0Ah batteries may need to be used without Smart Memory Switch remember last mode used 5 x Battery level & charging indicators
 - Unilite 14.8V 5.2Ah battery available to purchase separately

Memory Switch - remember last mode used

Automatic switch-over from mains to battery in

the event of power failure (battery installation

2A USB Powerbank - works with any battery

4 x Battery level & charging indicators

Comes with 5 metre heavy duty 24V-2.7A

NOTE: runtimes are based on using the Unilite 14.8V 5.2Ah battery. Runtimes with other batteries will vary.

LUMEN 5000LM | RUNTIME approx 2-15H | BEAM 49M | IP RATING IP65/IK10

Installed

MTB-5300 MULTI BATTERY 'HYBRID' SITE LIGHT

- 5300 lumen 50W 6500K COB LED
- Dual Power - rechargeable & mains powered
- Takes up to 20V 6.0Ah batteries from Milwaukee. De Walt, Makita & Metabo - 4 adapters included
- Secure battery compartment cover (note: larger 6.0Ah batteries may need to be used without cover)
- Super tough heavy duty nylon construction
- Easy carry rubber grip handle
- 180° Rotating stand with holes for attaching tripod/ magnet
- 4 x dim settings: 650 / 1350 / 2700 / 5300 lumen
- IP65 Dust & water resistant / IK07 Shock proof

BATTERY Not included, bare tool WEIGHT 1250g DIMENSIONS W 238 x H 257 x D 181mm

H05RN-F power lead/charger (includes UK, EU, US

LUMEN 5300LM | RUNTIME approx 2.5-16H | BEAM 95M | IP RATING IP65/IK07

MTB-10000 MULTI BATTERY 360° SITE LIGHT

- 10000 lumen 6500K SMD LEDs
- Multiple colour temperatures CCT: 2700k / 3500k / 4500k / 5500k / 6500k
- Takes up to 20V 6.0Ah batteries from Milwaukee, De Walt, Makita & Metabo - 4 adapters included
- Secure battery compartment cover (note: larger 5.5Ah-6.0Ah batteries may need to be used without • Smart Memory Switch - remember last mode used cover)
- Super tough heavy duty nylon & polycarbonate construction

| ERY | Not included, |
|--------|---------------|
| HT | 3650g |
| NSIONS | W 278 x H 25 |

LUMEN 10000LM | RUNTIME approx 1-10H | BEAM 89M | IP RATING IP65/IK08















& AU plugs) Unilite 14.8V 5.2Ah battery available to purchase separately (NOTE: Only Unilite battery can be charged via the lamp)

NOTE: runtimes are based on using the Unilite 14.8V 5.2Ah battery. Runtimes with other batteries will vary.

required) for added safety



BATT

WEIG

DIME

bare tool x D 333mm

- Milky diffuser lens for even light dispersion
- Easy carry rubber grip handle Concealed fold-out ultra tough steel hanging hook
- in base
- 2 screw holes in base for attaching magnets
- Heavy duty IK08 Shock proof
- 5 x Battery level & charging indicators
- Unilite 14.8V 5.2Ah battery available to purchase separately





TL-6000 SUPER TOUGH TRIPOD LIGHT

- 6000 lumen 6500K SMD LEDs
- Multiple colour temperatures CCT: 2700k /
- 3500k / 4500k / 5500k / 6500k
- Dual Power rechargeable & mains powered 2 Independent heads fold-out 90° and pivot 330° for
- light direction where its required Super tough heavy duty nylon, polycarbonate &

aluminium construction BATTERY WEIGHT DIMENSIONS

14.8v 5200mAh Li-ion 4400a Folded: W 142 x H 1200 x D 142mm **<u>T</u>UNILITE**

- Quick release set-up & fold for rapid deployment
- Extends to 2.24m & folds down to 1.2m
- Smart Memory Switch remembers last mode used
- High capacity 14.8V 5200mAh Li-ion battery
- 5 x Battery level and charging indicators
- Mains 20V-1.1A multi-country charger/power lead included (inc UK, EU, US & AU adaptors)
- Quick 4.5 hour charge time

Anti-slip rubber grip handle

Super strong magnetic base

4-5 hours charge time

Adjustable head to change light angle

Acrylic LED diffuser for even light dispersion

included (inc UK, EU, US & AU adaptors)

Mains 12V-2A multi-country charger/power lead

SLR-5500 RECHARGEABLE SITE LIGHT

- 5500 lumen 50W white SMD LEDs, 6500k
- High power 7.4v 7500mAh Li-ion battery Removable battery with powerful 2A USB power bank with battery level and charging indicators
- Dual Power rechargeable & mains powered
- Tough aluminium & polycarbonate construction
- Glow-in-the-Dark strip around reflector

7.4v 7500mAh Li-ion Battery Pack BATTERY WEIGHT 2200g DIMENSIONS 215 x 192 x 285mm

LUMEN 5500LM | RUNTIME 3-6H | BEAM 54M | IP RATING IP54

LUMEN 6000LM | RUNTIME 2-16H | BEAM 64M | IP RATING IP65/IK07

RL-5250 INDUSTRIAL 360° LED LANTERN

- 5250 lumen 50W 160 x SMD LEDs, 6500k
- Dual Power rechargeable & mains powered
- 360° and 180° Lighting modes
- dispersion

11.1v 5200mAh Li-ion 1820a Ø157.5 x H 285.6 mm

- Concealed ultra tough hanging hook in the base
- Screw hole in the base for attaching to tripods
- High power 11.1v 5200mAh Li-ion battery
- Battery level and charging indicators
- Mains 15V-1.5A multi-country charger/power lead included (inc UK, EU, US & AU adaptors)
- Fast 3.5 hours charge time

Ultra tough nylon polymer construction Milky polycarbonate diffuser for even light Stainless steel carry handle on the top

DIMENSIONS

LUMEN 5250LM | RUNTIME 2-16H | BEAM 44M | IP RATING IP65/IK07

SLR-4400 DUAL POWER SITE LIGHT

- 4400 lumen 50W white COB LED, 6500k
- Dual Power rechargeable & mains powered
- Super tough IK07 aluminium & TPR construction Memory function - remembers last mode used
- 180° Vertical adjustable stand/handle
- Tripod & magnet mountable via hole in stand

BATTERY

WEIGHT

IP65 dust & water resistant

11.1v 5200mAh Li-ion 1150g DIMENSIONS 225 x 220 x 70mm

 Battery level and charging indicators Mains 15V-1.5A multi-country charger/power lead

included (inc UK, EU, US & AU adaptors) Quick 4 hour charge time

Powerful 11.1v 5200mAh integrated li-ion battery

- Magnet attachment and tripods available to
- purchase separately

LUMEN 4400LM | RUNTIME 2-9H | BEAM 74M | IP RATING IP65/IK07



















RF-5400 SUPER TOUGH FLOODLIGHT

- 5400 lumen 50W 6500K SMD LEDs
- Top quality LEDs with up to 100,000 hour lifespan
- Dual Power rechargeable and mains powered
- Super tough heavy duty nylon construction
- Low profile design for easy storage & transport
- Glare-free milky lens for extensive light spread
- Intelligent heat dissipating design
- 180° adjustable stand/handle with holes for tripod/ magnet (comes with long threaded screw)
- Memory function remembers last mode used
- IP65 dust & water resistant

BATTERY 11.1v 5200mAh Li-ion WEIGHT 1450g DIMENSIONS 273 x 205 x 81mm

- LUMEN 5400LM | RUNTIME 2-16H | BEAM 56M | IP RATING IP65/IK09



- 3300 lumen 30W 6500k COB LED
- Tough heavy duty Aluminium, TPR & nylon construction
- Low profile design for easy storage & transport
- Intelligent heat dissipating design
- 180° Adjustable stand with 2 sizes holes for
- attaching to tripods and the Unilite magnet 2A USB powerbank for charging devices
- Memory function remembers last mode used
- IP65 Dust & water resistant

| BATTERY | 7.4v 5200mAh Li-ion |
|------------|---------------------|
| WEIGHT | 940g |
| DIMENSIONS | 208 x 140 x 56mm |

LUMEN 3300LM | RUNTIME 3-25H | BEAM 79M | IP RATING IP65/IK07

RF-2000 HEAVY DUTY FLOODLIGHT

- 2000 lumen 15W 6500k COB LED
- Tough heavy duty Aluminium, TPR & nylon construction
- Low profile design for easy storage & transport
- Intelligent heat dissipating design
- 180° Adjustable stand with 2 sizes holes for attaching to tripods and the Unilite magnet
- 2A USB powerbank for charging devices

00mAh Li-ion 12 x 49mm

- Memory function remembers last mode used
- IP65 dust & water resistant

| BATTERY | 3.7v 52 |
|------------|----------------------|
| WEIGHT | 610g |
| DIMENSIONS | 172.5 x ⁻ |

LUMEN 2000LM | RUNTIME 3-25H | BEAM 56M | IP RATING IP65/IK07







www.unilite.co.uk

8

- imm
- IK07 Shock proof & 2m drop resistant Powerful 7.4v 5200mAh Li-ion battery

 IK07 shock proof & 2m drop resistant Powerful 3.7v 5200mAh Li-ion battery

battery warning 3x flash

• 5 Battery level & charging indicators, plus low

Im high quality USB-C charging cable (included)

2A USB-C charging - 3.5 hour charge time

IK09 shock proof & 2m drop resistant

Quick 3.5 hour charge time

purchase separately

• 5 x Battery level and charging indicators

included (inc UK, EU, US & AU adaptors)

Magnet attachment and tripods available to

Mains 15V-1.5A multi-country charger/power lead

- 5 Battery level & charging indicators, plus low battery warning 3x flash
- 2A USB-C charging 5.5 hour charge time
- Im high quality USB-C charging cable (included)



K-550 COMPACT MINI WORK LIGHT

- 550 lumen 5.7W white 6500K COB LED
- Press & Hold Turbo mode with additional red modes
- 6 different lighting modes Ultra tough nylon & polycarbonate construction
- Super compact and lightweight size
- 160° rotating stand with strong magnet
- Smart Memory remembers last mode used

BATTERY WEIGHT 74g DIMENSIONS

3.7v 1200mAh Li-polymer 54 x 28 x 60mm

- **<u>T</u>UNILITE**
- Glow-in-the-Dark strip around led
- Comes with a carabiner and handy storage bag
- Powerful 3.7v 1200mAh li-polymer battery
 - Useful battery level & charging indicators
 - Fast 1A USB-C charging 1.5 hour charge time
 - 30cm USB-C charging cable included

IK07 Shock proof - 2M drop resistant

Supports quick 'USB PD' Charging

Im high quality USB-C cable included

Powerful 3.7v 1500mAh Li-polymer battery Battery level & charging indicator LED under switch

Fast 3A USB-C charging - 2.5 hour charge time

*550 lumen is on Turbo mode and operates by 'press & hold' switch with 1 hour total runtime. High mode is 375 lumen with 3 hour runtime.

LUMEN 550LM | RUNTIME 1*-28H | BEAM 29M | IP RATING IPX6

WL-450R DUAL BEAM COMPACT WORK LIGHT

- 450 lumen 7W white 6500K COB LED
- Additional 450 lumen 3W 6500K CREE LED spot beam with magnifying collimator lens
- Ultra tough nylon & TPR construction
- 360° rotating stand/handle with super strong magnets
- Smart Memory remembers last mode used

| BATTERY | 3.7v 1500mAh Li-polyme |
|------------|------------------------|
| WEIGHT | 145g |
| DIMENSIONS | 69.5 x 34.1 x 85.7mm |

LUMEN 450LM | RUNTIME 2.5-6H | BEAM 34M | IP RATING IP65/IK07

SLR-1450 COMPACT WORK LIGHT

- 1450 lumen white COB LED, 6500k
- With 150 lumen 6500k white LED flashlight
- Plus 45 lumen Red and Red flash modes

- Battery level and charging indicators
- 2A USB-C charging 3 hour charge time
- Im high quality USB-C cable included
- Battery can be removed so a convenient spare can be kept at hand
- charged out of the lamp and used as a separate powerbank

288a folded 122.5 x 50.5 x 50.5mm / extended 219 x 50.5 x 50mm

LUMEN 1450LM | RUNTIME 3-90H | BEAM 53M | IP RATING IPX5

LUMEN 1750LM | RUNTIME 4.5-195H | BEAM 50M | IP RATING IPX5

SLR-1750 WORK LIGHT WITH POWERBANK

- 1750 lumen white COB LED, 6500k
- Red LED modes for emergency / signalling / night vision
- Built-in USB power bank with multiple intelligent outputs - 5V-3A/9V-2A/12V-1A
- Super tough copolymer and aluminium construction
- 180° rotating handle/stand with carabiner snap hook 1m high quality USB-C cable included

BATTERY WEIGHT DIMENSIONS 3.7v 10,400mAh Li-ion 600g folded - 158 x 102 x 55mm / extended - 268 x 102 x 48mm

- Strong magnets within the stand
- Glow-in-the-dark strip for extra visibility
- Super high power 'LG' 10,400mAh battery
- Battery level and charging indicators
- Faster 4 4.5 hour USB-C charging with multiple inputs - 5V-3A/9V-2A

www.unilite.co.uk 11






www.unilite.co.uk



10

- BATTERY WEIGHT DIMENSIONS
- Glow-in-the-dark strip for extra visibility
 - 3.7v 5000mAh 21700 Li-ion



Powerful 'LG' 3.7v 5000mAh 21700 Li-ion battery Super tough copolymer and aluminium construction 180° rotating handle/stand with carabiner snap hook 21700 battery has its own USB-C port so is easily Strong magnets within the stand





NL-350R | RECHARGEABLE NECK LIGHT

- 350 lumen 6500k white SMD LEDs
- Super lightweight, adjustable and comfortable
- 2 light heads can be adjusted independently
- Super tough nylon & polycarbonate construction
- Up to 120° wider lighting angle
- IK07 Shock proof 2m drop resistant
- IP54 Dust & water resistant
- Circuit protection prevents battery from overcharging or over-discharging

3.7v 700mAh Li-ion BATTERY WEIGHT 140g DIMENSIONS 230 x 150 x 23mm

- High quality 3.7v 700mAh Li-ion battery
- 3 colour LED battery level indicator
- Charging indicator Green flash: Charging / Green: Fully Charged
- Low battery 3x warning flash reminds when charging is needed
- IA USB-C charging cable included quick 2.5 hour charge time

250 lumen 6500k SMD LED flashlight with flashing

Im high quality USB-C charging cable included

IK07 Shock proof - 2m drop proof

IP65 Dust & water resistant

Super strong magnetic base

Sturdy rear metal pocket clip



PB-7800 POWERBANK WITH FLASHLIGHT

Industrial magnetic powerbank with flashlight

- High quality 3.7v 7800mAh Li-ion battery
- Super tough nylon and TPR construction
- Intelligent multiple outputs 5V-2.4A / 9V-2A / 12V-1.5A
- Fast 2A USB-C charging 5 hour charge time
- Over-charge, over-load, deep-discharge and shortcircuit protection
- Battery level and charging indicators

BATTERY WEIGHT 265g DIMENSIONS

- 3.7v 7800mAh Li-ion
- 114 x 65 x 32mm
- LUMEN 250LM | RUNTIME 35H | BEAM 21M | IP RATING IP65/IK07

LUMEN 350LM | RUNTIME 2-10H | BEAM 45M | IP RATING IP54/IK07

mode

L-1800 | DUAL LED LANTERN

- 1800 lumen white spot beam LED, 6500k
- Additional 1000 lumen COB LED floodlight, 6500k
- Red static & red flashing modes
- Super tough polycarbonate, ABS & aluminium construction
- Easy press dual switches for easy mode selection
- Threaded hole in the base for attaching to tripods
- Glow-in-the-Dark strip around reflector
- Convenient shoulder carry strap included
- Battery level & charging indicator LEDs

| BATTERY | 3.7v 18,000mAh Li-io |
|------------|----------------------|
| WEIGHT | 773g |
| DIMENSIONS | 108 x 200 x 131mm |

Super high power 18,000mAh li-ion battery Multiple USB power bank outputs - 5V-3A / 9V-2A

- / 12V-1A
- Intelligent multiple USB-C charging inputs 5V-3A / 9V-2A
- Faster 2A and 3A charging 8 or 7 hour charge time

12









IL-175R FOLDING INSPECTION LIGHT

- 175 lumen white COB LED, 6500k
- Secondary rear 150 lumen white COB LED, 6500k
- Extra top torch 70 lumen SMD LED, 6500k
- Ultra lightweight compact pocket size
- Memory function remembers last mode used
- 180° vertical folding head

Super tough nylon and aluminium construction

BATTERY 3.7v 350mAh Li-ion WEIGHT 60g DIMENSIONS

folded 111.5 x 19.2 mm / extended 225 x 19.2 mm

LUMEN 175LM | RUNTIME 3-6H | BEAM 21M | IP RATING IP20/IK07

Useful pocket clip

Useful pocket clip

charging is needed

298 x 26 x 20.6 mm

charging is needed

Strong magnetic base and dual rear magnets

Low battery 3x warning flash - reminds when

Strong magnetic base and dual rear magnets

Low battery 3x warning flash - reminds when

Quick 1A USB-C charging - 3 hour charge time

Im high quality USB-C cable included

Im high quality USB-C cable included

Quick 1A USB-C charging - 2.5 hours charge time

IL-375R | FOLDING INSPECTION LIGHT

- 375 lumen white COB LED, 6500k
- Secondary rear 250 lumen white COB LED, 6500k
- Extra top torch 100 lumen SMD LED, 6500k
- Ultra lightweight compact pocket size
- Memory function remembers last mode used
- 180° vertical folding head
- Super tough nylon and aluminium construction

| BATTERY | 3.7v 1100mAh Li-ion |
|------------|--|
| WEIGHT | 80.8g |
| DIMENSIONS | folded 156 x 33 x 20.6 mm / extended 2 |

LUMEN 375LM | RUNTIME 3-6H | BEAM 26M | IP RATING IP54/IK07

IL-425R | FOLDING INSPECTION LIGHT

- 425 lumen white COB LED, 6500k
- Secondary rear 150 lumen white SMD LED,
- 6500k

- Extra top torch 80 lumen SMD LED, 6500k
- Ultra lightweight compact pocket size
- 180° vertical folding head
- Super tough aluminium & nylon construction
- Useful pocket clip Super strong magnetic base IK07 shock resistant - 2m drop resistant
- Low battery 3x warning flash reminds when
- charging is needed
- Quick 1A USB-C charging 3 hour charge time
 1m high quality USB-C cable included

3.7v 1100mAh Li-ion

80.8q

folded 147 x 33.5 x 21 mm / extended 279 x 33.5 x 21 mm

LUMEN 425LM I RUNTIME 3-6.5H I BEAM 31M I IP RATING IP20/IK07

IL-925R | FOLDING INSPECTION LIGHT

- 925 lumen white COB LED, 6500k
- Secondary rear 475 lumen white COB LED, 6500k
- Extra top torch 150 lumen SMD LED, 6500k
- Compact hand-held and pocket size
- Memory function remembers last mode used
- 180° vertical folding head
- Super tough aluminium & nylon construction

BATTERY WEIGHT DIMENSIONS

3.7v 2600mAh Li-ion 193g

IK07 shock resistant - 2m drop resistant

- Super strong magnetic base
- IP54 dust & water resistant
- Battery level & charging indicators
- 1A USB-C charging 4 hour charge time
- Im high guality USB-C cable included

folded 162 x 40 x 29 mm / extended 304 x 33 x 29 mm



T<u>i linilite</u>



14

www.unilite.co.uk

- BATTERY WEIGHT DIMENSIONS













PL-3 INSPECTION PENLIGHT

- 275 lumen white SMD LEDs, 6500k
- Die cast aircraft grade aluminium construction
- Convenient compact pocket size
- Easy press rubberised micro-switch
- 3 Light mode settings Strong magnetic base

BATTERY WEIGHT DIMENSIONS

3 x 1.5v AAA Alkaline Batteries (inc.) 57g (without batteries) 154 x 15 x 21.5mm

LUMEN 275LM | RUNTIME 3-16H | BEAM 23M | IP RATING IPX4

IL-625R | INSPECTION LIGHT

- 625 lumen white 5W COB LED, 6500k
- 250 lumen white 3W SMD LED spot beam torch
- 395nm UV LED on the front
- Super tough aluminium & polycarbonate
- Rear magnetic pocket clip
- Strong integral magnets on back & base
- Glow-in-the-dark strip around LED

3.7v 2500mAh Li-ion BATTERY WEIGHT 190g DIMENSIONS 188 x 35 x 35mm

 Battery level & charging indicators High power 3.7v 2500mAh Li-ion battery

Useful rear aluminium pocket clip

IPX4 water resistant

Im drop resistant

- IA USB-C charging 3 hour charge time
- Im USB-C charging cable included

LUMEN 625LM | RUNTIME 3-12H | BEAM 46M | IP RATING IP65/IK07

IL-SIG1 | SIGNALLING INSPECTION LIGHT

- 1100 lumen white 10W SMD LEDs, 6500k
- Red / Amber / Green SMD LEDs for signalling
- Coloured LEDs have static & 2Hz flash modes
- 4 Independent switches for easy operation
- 220 lumen white 6500k SMD LED top torch Super tough aluminium & polycarbonate
- Built-in aluminium heat sink on the back

BATTERY WEIGHT 334g DIMENSIONS 205 x 60 x 42mm

3.7v 4400mAh Li-ion

- Rotating hanging hook with magnets
- Multi-positional fold-out kick stand/hook
- Red-to-Green charging indicator LED 4-5 hour charge time
- Im DC-USB charging cable included

LUMEN 1100LM | RUNTIME 3.5-30H | BEAM 61M | IP RATING IP54

CRI-1250R HIGH CRI INSPECTION LIGHT

- 1250 lumen 10W high CRI 96+ COB LED
- 3 Colour Temperatures CCT: 2700k/4500k/6500k
- Press and hold smooth dimming function
- 250 Lumen 3W SMD LED flood beam top torch
- 5W UV LEDs on front (385nm)
- Built-in power bank for charging devices

BATTERY

WEIGHT

Super tough aluminium & polycarbonate

3.7v 5000mAh Li-ion 406a 216 x 58 x 38mm DIMENSIONS

Strong integral magnets on back & base

- Retractable 360° rotating hanging hook Glow-in-the-dark strip around LED
- Battery level & charging indicators
- 2A USB-C charging 5 hour charge time
- Magnetic charging dock & 1m USB-C charging cable included

96 CRI

LUMEN 1250LM | RUNTIME 3-24H | BEAM 58M | IP RATING IP65/IK07





UNILITE





CRI-3350 HIGH CRI SITE LIGHT

- 3350 lumen 30W high CRI 96+ COB LED
- 5 Colour Temperatures CCT: 2700K / 3500K / 4500K / 5500K / 6500K
- Dual power rechargeable & mains powered Memory function - remembers last mode used
- Super tough aluminium, nylon & TPR structure
- Built in aluminium heat sink
- 180° adjustable stand/handle with hole for attaching

nAh Li-ion

74mm

| BATTERY | 11.1v 5200 |
|------------|------------|
| WEIGHT | 1150g |
| DIMENSIONS | 224 x 199 |

to tripod/magnet

- IK07 shock resistance
- Battery level & charging indicators
- Mains 5M 15V-1.5A 'quick release' multi-country charger/power lead included (inc UK, EU, US & AU adaptors)
- Fast 3.5 hours charge time

96 CR

<u>T</u>UNILITE

LUMEN 3350LM | RUNTIME 2.5-9H | BEAM 62M | IP RATING IP65/IK07

CRI-H200R HIGH CRI SENSOR HEADTORCH

- 200 lumen high CRI 96+ COB LED
- 3 Colour Temperatures CCT: 2500K / 4500K / 6500K
- Sensor mode for hands-free operation
- Super tough construction with rubberised coating
- 60° rotational head
- Adjustable non-slip silicone lined headband included

3.7v 1500mAh Li-Polymer BATTERY WEIGHT 110g DIMENSIONS headtorch 48 x 79 x 46mm IP65 dust & water resistant

4 x Helmet clips included

IP65 dust & water resistant

IK07 shock proof - 2m drop resistant

Useful battery level and charging indicator

IA USB-C charging - 4.5 hours charge time

IK07 shock proof - 2m drop resistant

Rechargeable 3.7v 2600mAh Li-ion battery

Useful battery level and charging indicator

IA USB-C charging - 4.5 hours charge time

90° rotational head

- IK07 Shock resistant
- Red-to-Green charging indicator Fast 1A USB-C charging - 2.5 hours charge time
- Im USB-C charging cable included



LUMEN 200LM | RUNTIME 3H | BEAM 27M | IP RATING IP65/IK07

HT-680R DUAL LED HIGH CRI HEADTORCH

- 680 lumen white spot beam CREE LED, 6500k
- Secondary 500 Lumen warm white flood beam high CRI 90+ CREE LED, 4500k
- Memory function remembers last mode used
- Super tough construction with top quality cables
- and rubberised coating Adjustable non-slip silicone lined headband included
 1m USB-C charging cable included
- BATTERY WEIGHT 175g DIMENSIONS

3.7v 2600mAh Li-Ion Battery headtorch 56 x 35 x 25mm / battery pack: 86 x 36 x 37 mm

90 CR

LUMEN 680LM I RUNTIME 4-30H I BEAM 89M I IP RATING IP65/IK07

HT-900R | HIGH POWER INDUSTRIAL HEADTORCH

- 900 lumen white CREE LED, 6500k
- Wide angle light spread with bright central spot
- Super tough construction with top quality cables
- Memory function remembers last mode used
- Adjustable non-slip silicone lined headband included 1m USB-C charging cable included 4 x Helmet clips included
- 72° rotational head

BATTERY WEIGHT DIMENSIONS

3.7v 2600mAh Li-lon Battery 185g headtorch 44 x 39 x 46mm / battery pack: 86 x 36 x 37 mm

LUMEN 900LM | RUNTIME 4.5-100H | BEAM 82M | IP RATING IP65/IK07



UNILITE

UNILITE




UNILITE

LINILITE







- 1100 lumen white CREE LED, 6500k
- Easy twist smooth dimming switch
- Retractable shield to provide spot & flood beams 2 x High power 18650 2600mAh Li-ion batteries
- included Intelligent parallel circuitry - works with 1 or 2 batteries

BATTERY WEIGHT DIMENSIONS 2 x 3.7v 2600mAh 18650 Li-ion (inc.) 275g (with 2 batteries) headtorch 38 x 60 x 45mm / battery pack 53 x 90 x 45mm

LUMEN 1100LM | RUNTIME 4-148H | BEAM 167M | IP RATING IPX6

PS-HDL9R HIGH POWER INDUSTRIAL HEADTORCH

- 750 lumen white CREE LED, 6500k
- Red rear battery pack light (ON & FLASH)
- Intelligent parallel circuitry works with 1 or 2 batteries
- Anti-dazzle retractable light shield
- Super wide angle light spread
- Easy twist smooth dimming power switch

| BATTERY |
|------------|
| WEIGHT |
| DIMENSIONS |

2 x 3.7v 2000mAh 18650 Li-ion (inc.) 275g (with 2 batteries) headtorch 38 x 60 x 45mm / battery pack 65 x 90 x 45mm

LUMEN 750LM I RUNTIME 4-260H I BEAM 100M I IP RATING IPX6

HT-650R | DUAL POWER DUAL LED HEADTORCH

- 650 lumen white COB LED, 6500k
- Circular COB LED for wide flood lighting
- Additional 450 lumen CREE LED spot beam, 6500K
- Dual Power rechargeable or 3 x AAA batteries
- Memory function remembers last mode used
- Super tough construction with rubberised coating
- 60° rotational head
 - 3.8v 1100mAh Li-Polymer Battery (inc) or 3 x 1.5v AAA Alkaline Batteries (not inc.)

BATTERY WEIGHT DIMENSIONS

89a headtorch 46.3 x 68.7 x 40mm

LUMEN 650LM I RUNTIME 2-30H I BEAM 84M I IP RATING IP65/IK07

HL-8R DUAL BEAM SENSOR HEADTORCH

- 475 lumen white SMD LEDs, 6500k

- Super tough construction with rubberised coating
- IK07 shock resistant

BATTERY WEIGHT DIMENSIONS

ONAUL

3.7v 1500mAh Li-Polymer 111g headtorch 47.5 x 78.5 x 46mm

LUMEN 475LM | RUNTIME 4-35H | BEAM 90M | IP RATING IP65/IK07



UNILITY





www.unilite.co.uk

20



Fast 1A USB-C charging - 2.5 hours charge time Im USB-C charging cable included

Adjustable non-slip silicone headband included

Green flash-to-Green charging indicator light

IP65 dust & water resistant

Im impact resistant

60° rotational head

IK07 shock proof - 2m drop resistant

Im USB-C charging cable included

Rechargeable 3.8v Li-Po battery included

Red-to-Green charging indicator on battery

Fast 1A USB-C charging - 3.5 hours charge time

www.unilite.co.uk 21

LINILITE

Super tough construction with top quality cables

Super tough construction with top quality cables

 Useful battery level and charging indicators Im USB-C charging cable included

Presented in an EVA hard shell zipped case

 Adjustable non-slip silicone lined headband included Fast 2A USB-C charging - 3.5 hours charge time

Adjustable non-slip silicone lined headband included

Useful battery level and charging indicators

2A USB-C charging - 4.5 hours charge time

Im USB-C charging cable included Presented in an EVA hard shell zipped case

Adjustable non-slip silicone lined headband included

45° rotational head

45° rotational head

- 2 x Side SMD LEDs for wide flood lighting • 250 lumen SMD LED for long distance spot beam
- Sensor mode for hands-free operation













- 350 lumen white SMD LEDs, 6500k
- Network Rail Approved
- Dual Power rechargeable battery included or 3 x AAA batteries
- 3M VHB adhesive helmet mount (included)
- Adjustable non-slip silicone lined headband included
- Anti-dazzle retractable light shield

BATTERY WEIGHT DIMENSIONS 3.7v 1800mAh Li-Polymer (inc.) or 3 x AAA Battery Cartridge (batteries not inc.) 86g (with lithium battery) / 94g (with 3 x AAA batteries) headtorch 50 x 65 x 45mm

45° rotational head

hour charge time

3 x AAA battery cartridge included

Direct charging removable battery - 1A USB-C with 4

Spare batteries can be purchased separately

Battery level & charging indicator

Im USB-C charging cable included

LUMEN 350LM | RUNTIME 2-59H | BEAM 27M | IP RATING IPX6

HL-4R USB HELMET HEADTORCH

- 275 lumen white CREE LED, 6500k
- 2 x 5mm red LEDs for night vision static & flashing modes
- Easy push micro switch
- 45° rotational head
- Ultra-smooth reflector for long distance beam
- Super lightweight design

BATTERY 3.7v 1800mAh Li-Polymer WEIGHT 78g DIMENSIONS headtorch 63 x 40 x 42mm

- Strong ABS housing 1m impact resistant
- Adjustable non-slip silicone lined headband included

<u>T</u>UNILITE

- 3M VHB adhesive helmet mount included
- Useful drawstring bag included
- Red-to-Green charging indicator
- Fast 1A USB-C charging 2.5 hour charge time
- Im USB-C charging cable included

| LUMEN 275LM | Т | RUNTIME 6.5-170H | Т | BEAM 95M | Т | IP RATING IPX5 |
|-------------|---|-------------------------|---|-----------------|---|-----------------------|

PS-HDL2 HELMET HEADTORCH

- 200 lumen white CREE LED, 6500k
- 2 x 5mm LEDs for floodlight modes
- Easy push micro switch
- Ultra-smooth reflector for long distance beam
- 45° rotational head
- 3 x AAA Energizer alkaline batteries included
- Super lightweight design

- Strong ABS housing
- Im impact resistant
- IPX6 water resistant
- Adjustable non-slip silicone lined headband included
- 3M VHB adhesive helmet mount included

BATTERY WEIGHT DIMENSIONS

3 x 1.5v AAA Energizer Alkaline Batteries (inc.) 88g (with batteries) headtorch 47 x 62 x 37mm

LUMEN 200LM | RUNTIME 5-185H | BEAM 95M | IP RATING IPX6

LUMEN 250LM | RUNTIME 2-30H | BEAM 13M | IP RATING IPX5

BLT-1 USB BEANIE LIGHT

- 250 lumen white COB LEDs, 6500k
- Red 625nm static & flashing modes
- Light is easily removed from hat
- Built-in USB-A connector with protective cover
- Directly charged via a USB port
- High guality 3.7v 420mAh li-po battery
- Super fast charge time 1.5 hours

| BATTERY | 3.7v 420mA |
|------------|----------------|
| WEIGHT | 27g (light on |
| DIMENSIONS | 73.5 x 41 x 15 |

h Li-Polymer mm

- Red-to-Green charging indicator
- IPX5 water resistant
- Comfortable knitted Beanie, one size fits all
- Fabric: 35% acrylic 65% polyester Machine washable at 30°

















www.unilite.co.uk

24



FR-400 | RIGHT ANGLE USB FLASHLIGHT

- 400 lumen white LED, 6500k
- Hard anodized die cast matte aluminium body
- Head rotates to 90-degree angle
- Useful pocket clip and strong magnetic base
- Rubberised easy press side switch
- 2 light mode settings Frosted lens for smoother beam spread

BATTERY WEIGHT DIMENSIONS 3.7v 750mAh 10900 Li-ion (inc.) 90g (with li-ion battery) / 69g (without battery) Extended length 161.5 x Ø 19x Ø 17mm

LUMEN 400LM | RUNTIME 2-8H | BEAM 60M | IP RATING IP65

FR-1200 DUAL POWER RIGHT ANGLE FLASHLIGHT

- 1200 lumen white LED, 6500k
- Hard anodized die cast matte aluminium body
- Head rotates to 90-degree angle
- Useful pocket clip and strong magnetic base
- Rubberised easy press side switch
- 3 light mode settings
- Flawless smooth reflector for long distance beam
- Impact resistant to 2m

BATTERY WEIGHT DIMENSIONS

WEIGHT

DIMENSIONS

3.6v 2600mAh 18650 Li-ion (inc.) / or 2 x CR123A batteries (not inc.) 209g (with li-ion battery) / 161g (without battery) Extended length 160.5 x Ø 30x Ø 27mm

LUMEN 1200LM I RUNTIME 3-14H I BEAM 180M I IP RATING IP65

F-1400 DUAL POWER ALUMINIUM FLASHLIGHT

- 1400 lumen white LED, 6500k
- Hard anodized die cast matte aluminium body
- Tactical rubberised tail switch
- 4 light modes and 8Hz defence strobe
- Flawless smooth reflector for long distance beam
- Battery level and charging indicator LED

BATTERY

3.6v 2600mAh 18650 Li-ion (inc.) / or 2 x CR123A batteries (not inc.) 157g (with li-ion battery) / 109g (without battery) 140 x Ø 30x Ø 25mm

LUMEN 1400LM | RUNTIME 2.5-23H | BEAM 180M | IP RATING IP68

F-2700 USB ALUMINIUM FLASHLIGHT

- 2700 lumen white LED, 6500k
- Hard anodized die cast matte aluminium body
- Tactical rubberised tail switch
- 4 light modes and 8Hz defence strobe
- Flawless smooth reflector for long distance beam
- IP68 dust and waterproof 1m submersible
- Impact resistant to 2m

BATTERY WEIGHT DIMENSIONS

3.6v 5000mAh 21700 Li-ion (inc.) 210g (with li-ion battery) / 138g (without battery) 153 x Ø 33x Ø 28mm

LUMEN 2700LM | RUNTIME 3-45H | BEAM 218M | IP RATING IP68

Built-in rubberised USB-C charging port

Built-in rubberised USB-C charging port

charging or over-discharging 1A USB-C charging - 2.5 hour charge time

Circuit Protection prevents battery from over-

High quality USB-C charging cable inc. (0.5m)

Battery level and charging indicator under the switch

Battery level and charging indicator under the switch

T<u>i linilite</u>

- Circuit Protection prevents battery from overcharging or over-discharging
- IA USB-C charging 2.5 hour charge time High quality USB-C charging cable inc. (0.5m)
- Can also work with 2 x CR123A lithium batteries (not inc.)

Impact resistant to 2m

- High guality USB-C charging cable inc. (0.5m)
 - inc.)

IA USB-C charging - 2.5 hour charge time

Can also work with 2 x CR123A lithium batteries (not



Built-in concealed USB-C charging port

Battery level and charging indicator LED

charging or over-discharging


Safety nylon wrist strap included

Circuit Protection prevents battery from over-

Fast 2A USB-C charging - 3 hour charge time

High guality USB-C charging cable inc. (0.5m)

 Circuit Protection prevents battery from overcharging or over-discharging









ATEX-FL4 | INTRINSICALLY SAFE FLASHLIGHT

- 150 lumen white CREE LED, 6500k
- ATEX Zone O gas compliant
- Safety release valve to release hydrogen gases
- Chemical and corrosion resistant
- Rubberised head & handle for greater durability
- Industrial strength polycarbonate housing
- Detachable pocket clip included for hands free use
- Safety locking battery compartment

BATTERY WEIGHT DIMENSIONS 4 x 1.5v AA Alkaline Batteries (not inc.) 115g (without batteries) 174 x 47 x 47mm

REACH CE ROHS

Polycarbonate lens and smooth reflector for long

Optional brackets available for helmets

Safety locking battery compartment

Easy push micro switch operation

IP54 dust and water resistant

distance beam

3m submersible

IP67 dust and waterproof

LUMEN 150LM | RUNTIME 6-69H | BEAM 235M | IP RATING IP67

ATEX-RA2 INTRINSICALLY SAFE RIGHT ANGLE TORCH

- 350 lumen white CREE LED, 6500k
- ATEX Zone O gas compliant
- Suitable for mining
- Safety release valve to release hydrogen gases
- Chemical and corrosion resistant
- Rubberised head and grips for durability
- Ultra strength polycarbonate housing
- Convenient rear stainless steel pocket clip

BATTERY WEIGHT DIMENSIONS 4 x 1.5v AA Alkaline Batteries (not inc.) 250g (without batteries) 183 x 69 x 63mm ECEX EX

LUMEN 350LM | RUNTIME 6.5-13H | BEAM 288M | IP RATING IP54

ATEX-H2 INTRINSICALLY SAFE HEADTORCH

- 225 lumen white CREE LED, 6500k
- ATEX Zone 0 gas compliant
- Safety release valve to release hydrogen gases
- Strong ABS housing with durable synthetic rubber coating
- Safety locking battery compartment
- Easy press rubberised switch
- 2 mode light settings

BATTERY WEIGHT DIMENSIONS 3 x 1.5v AAA Alkaline Batteries (not inc.) 130g (without batteries) headtorch 80 x 50 x 45mm

- Adjustable non-slip silicone lined headband included
 JD67 dust and waterproof
- IP67 dust and waterproof
- 1m submersible

90° rotational head



LUMEN 225LM | RUNTIME 5-12H | BEAM 115M | IP RATING IP67







GUNRITE MERRY



ZFJ ZIPPED FLEECE LINED JUMPER

- 260gsm thick 100% polyester black zipped jumper for warmth and protection
- Brushed fleece lining for warmth in the harshest conditions
- Reflective silver details for enhanced visibility and safety
- Unilite branded YKK 'reversed' zippers
- Windbreaker flap behind main zip, providing extra layer against chilling gusts
- Elasticated cuffs to keep out sleeve drafts
- Additional soft lining around collar for added comfort
- Combines a practical working jacket with style
- Suitable for both work and leisure

SIZES AVAILABLE Small | Medium | Large | XL | 2XL | 3XL

LWJ | LIGHTWEIGHT PADDED JACKET

- Warm padded lightweight design
- 60gsm 100% nylon shell for superior water resistance
- 100% Polyester padding provides extra layer of insulation for added warmth.
- Warm brushed fleece lining for added comfort
- Soft fleece lining around collar.
- Unilite branded YKK 'reversed' zippers
- Elasticated cuffs to keep out sleeve drafts
- Windbreaker flap behind main zip, providing extra layer against chilling gusts

- High-vis yellow colouring and reflective silver piping for added safety
- Combines a practical working jacket with style
- Suitable for both work and leisure

SIZES AVAILABLE Small | Medium | Large | XL | 2XL | 3XL

WPC WIND & WATERPROOF COAT

- Triple layered water and windproof coat
- Engineered to keep you dry and shieled from the elements
- Outer shell constructed from 94% polyester and 6%
 Windbreaker flap behind main zip, providing extra spandex for durability and flexibility
- Internal layers made of 100% polyester bonded material with additional seam tape for enhanced wind and water resistance
- Peaked hood with elastic pull cords and high-rise collar for a secure seal against wind and rain
- Hood can easily be removed with detachable pop studs

- Elastic cord around bottom hem with two side pushrelease adjusters for a customisable fit
- Unilite branded YKK 'reversed' zippers
- layer against chilling gusts
- Reflective silver details for enhanced visibility and safety
- Underarm zips for extra ventilation on hot days
- Combines a practical working jacket with style
- Suitable for both work and leisure



www.unilite.co.uk

TUNILITE



DP-1B | HEAVY DUTY STORAGE POUCHES

- Super heavy duty set of 2 storage zip pouches
- Made from 600D ultra tough PVC impregnated nylon
- Thick waterproof lining on the inside
- Large mesh windows on the front
- Heavy duty Unilite branded #8 YKK zippers
- Stylish black reflective strips for added safety
- With extra silver reflective branding details
- Additional Velcro flap pockets on the back
- External Unilite branded snap-hook carabiners

DIMENSIONS Small: H 150 x W 230mm | Large: H 180 x W 200mm

OP-2B | HEAVY DUTY STAND-UP STORAGE POUCHES

- Super heavy duty set of 2 storage zip pouches
- Made from 600D ultra tough PVC impregnated nylon
- Thick waterproof lining on the inside
- Large mesh windows on the back
- Heavy duty Unilite branded #8 YKK zippers
- Stylish black reflective strips for added safety
- With extra silver reflective branding details
- External Unilite branded snap-hook carabiners
- Reinforced 60mm base depth allows pouches to stand-up

DIMENSIONS Small: H 150 x W 210mm | Large: H 200 x W 250mm



TI UNILITE

OP-3B SUPER HEAVY DUTY STORAGE POUCH

- Super heavy duty storage zip pouch
- Made from 900D ultra tough PVC impregnated nylon
- Large main internal compartment with extra thick padded waterproof lining
- Extra heavy duty Unilite branded #10 YKK zipper
- Super heavy duty waterproof exterior layer around the base & sides
- Large mesh expanding window pocket on the front
- Stylish black reflective strips for added safety
- With extra silver reflective branding details
- Mixture of 5 additional Velcro flap & Zip pockets using #8 YKK zippers
- 2 External 'D' rings attached using marine grade stainless steel rivets
- Comes with a 12Kn carabiner and A6 waterproof stone paper notebook

DIMENSIONS H 270 x W 190 x D 110mm







- Heavy duty stainless steel, ABS & TPR construction
- 8 x 18mm snap-off SK2 black steel blade
- Multi-position retractable quick slide button with auto-lock mechanism
- 2 x replacement snap-off blades conveniently stored inside
- Quick and easy blade change
- Convenient hole for attaching a lanyard

WEIGHT 100g | DIMENSIONS Length: 167mm

KC2 | HEAVY DUTY KNIFE CUTTER

- Heavy duty nickel, TPR and ABS construction
- Retractable SK5 black steel blades
- 4 replacement blades conveniently stored inside
- Multi-position retractable quick slide button
- Sliding locking button mechanism
- Quick release blade change
- Convenient hole for attaching a lanyard
- Accepts most standard utility blades

WEIGHT 183g | DIMENSIONS Length: 185mm

UK1 | FOLDING UTILITY KNIFE

- Heavy duty nickel, TPR and ABS construction
- 4 x SK5 black steel blades included
- 3 replacement blades conveniently stored inside
- Multi-positional folding design
- Easy press unlocking button
- Quick release blade change
- Convenient wire/strap cutter slot
- Useful hole for attaching a lanyard
- Accepts most standard utility blades
- Folded length: 116mm



DUNILITE





FK3 HEAVY DUTY FOLDING UTILITY KNIFE

- Heavy duty folding utility knife
- High-carbon 3Cr13 stainless steel blade
- 'Clip point' blade with serrated edge and tapered spine swedge
- Blade spine includes thumb rise for extra grip
- Blade hardness 52-54 HRC
- Assisted one-handed opening with thumb studs
- Easy to operate one-handed 'Liner lock' mechanism
- Ultra tough ergonomic aluminium handle with front Quillion finger guard

WEIGHT 119.5g | DIMENSIONS Extended Length: 198mm

EK4 HEAVY DUTY FOLDING UTILITY KNIFE

- Heavy duty folding utility knife
- High-carbon 3Cr13 stainless steel blade
- 'Drop point' blade with serrated edge and tapered spine swedae
- Blade spine includes thumb rise for extra grip and 2 wire stripper notches
- Assisted one-handed opening with thumb studs
- Blade hardness 52-55 HRC
- Ultra tough ergonomic aluminium handle with front Quillion finger guard
- Easy to operate one-handed 'Framelock' mechanism

Ultra tough ergonomic aluminium handle

Hole in the handle for adding a lanyard

Super low-profile at only 10mm thick





EK5 | HEAVY DUTY FOLDING UTILITY KNIFE

- Heavy duty folding utility knife
- Super high-carbon 7Cr17MoV stainless steel blade with high tensile strength
- 'Sheepsfoot' blade with cable stripper notch
- High blade hardness 56-58 HRC
- Crescent nail pull in the blade spine for easy opening
- Sharpening 'choil' notch at the blade plunge line for easier sharpening
- Durable and easy to operate 'Lockback' mechanism

WEIGHT 107g | DIMENSIONS Extended Length: 182mm

WEIGHT 135g | DIMENSIONS Extended Length: 195mm



- Pocket clip for easy carrying



- Pocket clip for easy carrying
 - Hole in the handle for adding a lanyard



3LITINT



ES-6 | HEAVY DUTY 6" ELECTRICIANS SCISSORS

- Ultra tough 6" professional electricians scissors (160mm)
- Whole steel frame for high resistance & durability
- Industrial strength polypropylene handles with full TPR coating for superior grip & comfort
- High grade 4034 Japanese stainless steel 4.0mm thick polished blades with 40mm cutting edge
- Black 'DLC' (diamond-like-carbon) coating on blades for extra sharpness
- High hardness blades (58±2 HRC) with anti-slip serrated edge
- 2.5mm² & 1.5mm² wire strippers & wire crimping terminal
- Notch in the blades for cutting/stripping 50mm² cable

WEIGHT 153g | DIMENSIONS Length: 160mm | Blade Length: 40mm





MFS-8 | HEAVY DUTY 8" MULTI-FUNCTION SCISSORS

- Ultra tough 8" professional multi-function scissors (205mm)
- Industrial strength polypropylene handles
- With added TPR moulding for superior grip & comfort
- High grade 420 J2 Japanese stainless steel 3.0mm thick polished blades with 60mm cutting edge
- Black 'DLC' (diamond-like-carbon) coating on blades for extra sharpness
- High hardness blades (53±2 HRC) with anti-slip serrated edge
- Extra functions include safety box cutter, wire cutter notch and jar opener/nut cracker
- Includes polypropylene safety sheath
 - WEIGHT 142g | DIMENSIONS Length: 205mm | Blade Length: 60mm

- Includes heavy duty nylon clip-on belt sheath
- Suitable for cutting aluminium, copper and soft cable

Suitable for cutting soft materials such as tin sheets,

carpets, corrugated cartons, aluminium sheets,

plastics, CD, cards... etc.

37

www.unilite.co.uk



MT5M1 | HEAVY DUTY TAPE MEASURE

- Heavy duty 5m tape measure with 19mm wide blade
 Durable rear pocket clip wont detach even if screw
- High performance nylon coated blade
- 1.8m/6ft high stand-out blade
- Double riveted carbon steel hook
- Dual colour double sided imperial & metric blade
- Powerful push lock secures the blade
- Superior internal mechanism provides smooth operation
- loosens
- Impact resistant TPR covered ABS casing
- Drop tested from 1.5m
- WEIGHT 179g | DIMENSIONS H 69.5 x W 71 x D 41mm

MT5M4SL | HEAVY DUTY TAPE MEASURE

- Heavy duty 5m tape measure with 19mm wide blade
 Durable rear pocket clip wont detach even if screw
- Automatic self-lock secures the blade, with easy press button to release
- High performance nylon coated blade
- 1.8m/6ft horizontal stand-out blade
- Double riveted carbon steel hook
- Dual colour double sided imperial & metric blade
- Superior internal mechanism provides smooth operation
- loosens
- Impact resistant TPR covered ABS casing
- Drop tested from 1.5m

- WEIGHT 240g I DIMENSIONS H 74 x W 81 x D 42mm

MT5M2 HEAVY DUTY TAPE MEASURE

- Heavy duty 5m tape measure with 27mm wide blade
- Ultra high performance double nylon coated 'SUPERBLADE' gives 5 x extended life
- 2.9m/9.5ft horizontal stand-out blade
- SUPERBLADE withstands durability tests of falling sand particles with 60 litres of salt spray for 100 hours
- Magnetic triple riveted stainless steel dual hook with 1kg suction capacity
- Dual colour double sided imperial & metric blade
- Durable rear pocket clip wont detach even if screw loosens
- Powerful push lock secures the blade
- Superior internal mechanism provides smooth operation
- Impact resistant TPR covered ABS casing Drop tested from 9m

WEIGHT 322g | DIMENSIONS H 76.5 x W 79 x D 51.8mm

MT8M3 SUPER HEAVY DUTY TAPE MEASURE

- wide blade
- sand particles with 60 litres of salt spray for 100 hours
- Magnetic triple riveted stainless steel dual hook with 1kg suction capacity
- Dual colour double sided imperial & metric blade
- Durable rear pocket clip wont detach even if screw loosens
- Powerful push lock secures the blade
- Superior internal mechanism provides smooth operation
- Impact resistant TPR covered ABS casing
- Drop tested 12 times from 3m



INILITI

ABUILTTON



TUNILITE







- Super heavy duty 8m tape measure with 32mm
- Ultra high performance double nylon coated 'SUPERBLADE' gives 5 x extended life
- 4m/13ft horizontal stand-out blade
- SUPERBLADE withstands durability tests of falling

UNILITE

SG-YIO SAFETY GLASSES - INDOOR/OUTDOOR LENSES

D<u>I</u>UNILITE

- LENS MARKINGS
- Lens Filters: 2 (UV EN170) 1.4 (Indoor & Outdoor)
- Optical Class: 1 (high optical quality)
- Lens Coatings: Standard Anti-Scratch & Anti-Fog
 - Mechanical risk Low energy impact F
 - High speed particles at extreme temperatures T

WEIGHT 33.5g

Flexible PC & TPR co-injected side arms Rubberised TPR inner arm grips

Super tough flexible nylon-polymer frame

Toughened polycarbonate lenses

Indoor & outdoor mirror lens coating

Anti-scratch & anti-fog lens coatings

With 99% UV A/B/C protection (EN170)

8-Base curved toughened polycarbonate lenses

- TPR non-slip nose grip with reinforced bridge Side TPR temple shields with ventilation
- Micro-fibre drawstring storage bag included

CERTIFICATIONS CE/UKCA - EN166 | USA - ANSI Z87.1 | AU/NZ - AS/NZS 1337.1

SG-YCB | SAFETY GLASSES - CLEAR BLUE LIGHT LENSES

- Tough flexible polycarbonate frame
- 8-Base curved toughened polycarbonate lenses
- Clear 420Cut blue light blocking lenses
- Blocks harmful HEV blue light up to 420nm
- K & N anti-scratch & anti-fog lens coatings
- 99% UV A/B/C protection (EN170)
- Flexible PC & TPR co-injected side arms
- Adjustable rubberised non-slip nose pads
- Reinforced nose bridge
- Micro-fibre drawstring storage bag included

LENS MARKINGS

- Lens Filters: 2C (UV EN170) 1.2 (Clear)
- Optical Class: 1 (high optical quality)
- Lens Coatings: Anti-Scratch K Anti-Fog N
- Mechanical risk: Low energy impact F
 - High speed particles at extreme temperatures T

WEIGHT 28.5g



CERTIFICATIONS CE/UKCA - EN166 | USA - ANSI Z87.1 | AU/NZ - AS/NZS 1337.1

SG-YDS | SAFETY GLASSES - DARK SMOKE LENSES

- Tough flexible polycarbonate frame
- 8-Base curved toughened polycarbonate lenses
- Dark smoke lens tinting
- K & N anti-scratch & anti-fog lens coatings
- 99% UV A/B/C protection (EN172)
- Flexible PC & TPR co-injected side arms
- Side temple ventilation
- Adjustable rubberised non-slip nose pads
- Reinforced nose bridge
- Micro-fibre drawstring storage bag included

LENS MARKINGS Lens Filters: 5 (UV EN172) 2.5 (Dark Smoke)

- Optical Class: 1 (high optical guality)
- Lens Coatings: Anti-Scratch K Anti-Fog N
- Mechanical risk: Low energy impact F
- High speed particles at extreme temperatures T

WEIGHT 28g



CERTIFICATIONS CE/UKCA - EN166 | USA - ANSI Z87.1 | AU/NZ - AS/NZS 1337.1

SG-YFG | SAFETY GLASSES - CLEAR LENSES & FOAM GASKET

- Tough flexible polycarbonate frame
- 8-Base curved toughened polycarbonate clear lenses
- Hytrel black back frame with EVA foam gasket
- K & N anti-scratch & anti-fog lens coatings
- 99% UV A/B/C protection (EN170)
- Flexible PC & TPR co-injected side arms
- With side temple ventilation
 - Adjustable TPR non-slip nose pads
 - Reinforced nose bridge
- Micro-fibre drawstring storage bag included

LENS MARKINGS

- Lens Filters: 2C (UV EN170) 1.2 (Clear)
- Optical Class: 1 (high optical quality)
- Lens Coatings: Anti-Scratch K Anti-Fog N
- Mechanical risk: Low energy impact F
- High speed particles at extreme temperatures T

WEIGHT 39.5g



40









UG-12C4 | HEAVY DUTY CUT-D IMPACT GLOVES

- Cut resistant gloves with full dorsal TPR impact protection
- Flexible lightweight design, TPR weighs less than 60g
- Heavy duty 15-Gauge high-performance polyethylene (HPPE) yarn interwoven with steel and glass fibres for added strength and high cut resistance
- Sandy nitrile half-dip coating offers excellent grip
- TPR is sonic welded to the glove for greater longevity
- Adjustable TPR velcro wrist strap for secure fit
- Synthetic leather stitched cuff for durability
- Touch screen technology

- EN 388:2016 mechanical hazard protection: 4X42DP
 cut level D
- ANSI/ISEA 138 impact resistant level 2
- ANSI cut resistant level A4
- Available in 5 EU sizes 7/S, 8/M, 9/L, 10/XL & 11/ XXL.

EN 388

4X42DP



CUT

T<u>I LINILITE</u>

CERTIFICATIONS EN ISO 21420:2020 | EN 388:2016+A1:2018 | ANSI/ISEA 2016 | ANSI/ISEA138:2019

UG-TW1 | THERMAL WATERPROOF GLOVES

- Warm thermal waterproof gloves
- Uses rPET polyester yarn that has been extruded from waste plastic bottles
- Superior quality soft & supple 0.7-0.8mm full grain goat leather
- Reinforced leather top of finger tips for extra durability
- Suitable for use in cold & wet environments due to waterproof HIPORA membrane
- Reflective silver strips for added visibility
- Elasticated 360° wrist for a secure warm fit
- Ergonomically designed for improved dexterity
- Touch screen technology in the thumb & index finger

- EN 388:2016 mechanical hazard protection: 2X32B
 cut level B
- EN 511:2006 protection against Cold hazards 22X
 Available in 5 EU sizes 7/S, 8/M, 9/L, 10/XL & 11/ XXL.



CERTIFICATIONS EN ISO 21420:2020 | EN 388:2016+A1:2018 | EN 511:2006

www.unilite.co.uk

UNILITE







- Ultra strong heavy duty magnet
- Made from steel and aluminium
- Locking wing nut securely holds a site light
- Can be used with the following Unilite site lights: CRI-2300, CRI-3350, SLR-4400, SLR-6000, RF-2000, RF-3300, RF-5400, MTB-5000, MTB-5300 & MTB-10000

WEIGHT 169g | DIMENSIONS H 37 x Ø 54mm

TRIPOD-360 MULTI-USE TRIPOD WITH MAGNETIC PLATE

- Can hold up to 4 work lights
- Extendable height range between 0.9-1.9m
- Work lights with magnets can be placed on top or underneath the top plate
- Toughened aircraft grade aluminium construction
- ABS stability feet to prevent slipping
- One tripod leg has an extra extending feature for uneven ground
- Quick assembly and dismantling using the central screw tightening height adjuster
- Can be used with the following Unilite magnetic site lights: SLR-3500 & SLR-5500.
- Can be used with the following site lights when used with the LARGE-MAGNET attachment: CRI-2300, CRI-3350, SLR-4400, SLR-6000, RF-2000, RF-3300, RF-5400, MTB-5000, MTB-5300 & MTB-10000

WEIGHT 4800g | DIMENSIONS 1460 x 1460 x 1930mm

TRIPOD-SW | SINGLE HEAD TRIPOD WITH WHEELS & BRAKES

- To hold a single work light
- Sturdy castor wheels for easy manoeuvrability with independent foot brakes
- Extendable height range between 0.7-1.8m
- Work lights can be screwed directly to the top of the tripod or simply hooked on, using the bracket
 Toughened aircraft grade aluminium construction
- Quick assembly and dismantling using easy twist ergonomic height adjusters
- Can be used with the following Unilite site lights: CRI-2300, CRI-3350, SLR-4400, SLR-6000, RF-2000, RF-3300, RF-5400, MTB-5000 & MTB-5300

WEIGHT 3500g | DIMENSIONS 1240 x 1240 x 1850mm

WEIGHT 2560g | DIMENSIONS 1240 x 1240 x 1800mm

TRIPOD-SGL | SINGLE HEAD TRIPOD

- To hold a single work light
- Extendable height range between 0.7-1.8m
- Work lights can be screwed directly to the top of the tripod or simply hooked on, using the bracket
 Toughened aircraft grade aluminium construction
- ABS stability feet to prevent slipping
- Quick assembly and dismantling using easy twist ergonomic height adjusters
- Can be used with the following Unilite site lights: CRI-2300, CRI-3350, SLR-4400, SLR-6000, RF-2000, RF-3300, RF-5400, MTB-5000 & MTB-5300







BUILT TOUGH

- O uniliteuk
- J uniliteuk
- X uniliteuk
- f uniliteuk
- in uniliteuk
- unilite

Unilite Limited

The LAB, Moons Moat Drive Redditch, Worcestershire B98 9FG - UK T: 00[44] 1527 584 344 E: sales@unilite.co.uk W: www.unilite.co.uk